

### *Assegnazione Chip Select Pin*

*X\_CS\_PIN 61 (Chip Select Pin)*  
*Y\_CS\_PIN 14 (Chip Select Pin)*  
*Z\_CS\_PIN 15 (Chip Select Pin)*  
*EXT0\_CS\_PIN 43 (Chip Select Pin)*  
*EXT1\_CS\_PIN 41 (Chip Select Pin)*  
*EXT2\_CS\_PIN 39 (Chip Select Pin)*

### *Configuration\_Motor\_Driver.h*

*De-Commentare la stinga su cui è stato installato il TMC2130*

```
//#define X_IS_TMC2130  
//#define X2_IS_TMC2130  
//#define Y_IS_TMC2130  
//#define Y2_IS_TMC2130  
//#define Z_IS_TMC2130  
//#define Z2_IS_TMC2130  
//#define E0_IS_TMC2130  
//#define E1_IS_TMC2130  
//#define E2_IS_TMC2130  
//#define E3_IS_TMC2130  
//#define E4_IS_TMC2130  
//#define E5_IS_TMC2130
```

### *De-Commentare*

```
#define SOFT_SPI_TMC2130  
#define HYBRID_THRESHOLD
```

*Se viene de-commentato **#define SOFT\_SPI\_TMC2130** andare in **Configuration\_Pins.h** e aggiornare i seguenti PIN*

```
SOFT_MOSI_PIN 75  
SOFT_MISO_PIN 74  
SOFT_SCK_PIN 76
```